



UNIT OF MEASURE in. (mm)	SCALE APPROX. 1" = 1' 25.4mm = 304mm
-----------------------------	--

864692 SHEET 1 OF 1
MCM 3.0L WITH SIDE MOUNTS

NOTES:

- (1) DIMENSIONS REQUIRE A MINIMUM 1/2 in. (13mm) CLEARANCE FOR MOTOR MOUNT DEFLECTION.
- (2) SELECT THE APPROPRIATE EXHAUST RISE-HEIGHT TO MAINTAIN A MINIMUM OF 11 in. (279mm) BETWEEN THE TOP OF THE EXHAUST ELBOW AND THE WATERLINE OF THE BOAT AT MAXIMUM RATED LOAD.
- (3) INNER AND OUTER SURFACES OF TRANSOM MUST BE PARALLEL WITHIN 1/8 in. (3mm) IN AREA COVERED BY TRANSOM PLATES AND REMAIN WITHIN TRANSOM THICKNESS LIMITS.
- (4) FOR EXACT LOCATION OF CAVITATION PLATE IN RELATION TO BOAT BOTTOM, REFER TO INSTALLATION INSTRUCTIONS.
- (5) NUMBERS INSIDE BRACKETS "[]" ARE IN MILLIMETERS.